






# **UniFi Protect G4 Dome Camera**





#### Mechanical

Dimensions	Ø109.2 x 64.5 mm (Ø4.3 x 2.5")
Weight	Without Mount: 370 g (13.05 oz) With Mount: 390 g (13.76 oz)
Enclosure Materials	Aluminum Alloy, Polycarbonate, Hard-Coated Dome
Mounting Materials	Polycarbonate, Stainless Steel
Weatherproofing	IPX4
Resistance	IK08

### Optics

Sensor	5 MP CMOS Sensor
Lens	Fixed Focal Length
View Angle	H: 86°, V: 60°, D: 111°
Night Mode	Built-in Light Sensor Built-in IR LED Illumination and IR Cut Filter

## Video

Video Compression	H.264
Resolution	2688 x 1512 (16:9)
Maximum Frame Rate	24 FPS
Image Settings	Brightness, Contrast, Sharpness, Saturation, Noise Reduction, 50/60 Hz

### System

Processor Specs	Ambarella Advanced Image Processing SoC
Memory Information	512 MB
Management Interface	UniFi Protect
Networking Interface	RJ45, 10/100/1000 Mbps Ethernet
Flash Memory Support	256 MB
Max. Power Consumption	5W
Power Method	802.3af PoE, 44-57VDC, 0.114-0.088A
Supported Voltage Range	44-57VDC
Link/Activity LED	Yes
Button	Factory Reset
Operating Temperature	-20 to 40° C (-4 to 104° F)



Operating Humidity	0 to 90% Noncondensing
Certifications	FCC, IC, CE
Audio	
Microphone	Yes (Can be Disabled in Software)
Speaker	Yes
Software	
Controller Software	UniFi Protect
Mobile Apps	UniFi Protect iOS and Android

